

Ultrasonics as a Method of Bird Control

D. M. Hamershock  
Windshield Systems Program Office (WL/FIVR)  
Wright-Patterson AFB, Ohio

ABSTRACT

The potential users of ultrasonic bird repelling devices are many and include: All branches of the military, airfield managers, biologists, pest control/maintenance employees, government agencies (the Federal Aviation Administration, the US Department of Agriculture), agri-/aquaculturalists, aircraft manufacturers, and homeowners. A literature search conducted to find reports addressing the efficacy of ultrasonic bird repelling devices (UBRDs) revealed several substantial efforts. This report compiles and presents the results of the literature search. Avian hearing physiology, ultrasonic sound characteristics and the physical effects of ultrasonics on biological systems are addressed.

(ULTRASONICS, BIRD, AIRCRAFT, BIRD STRIKE, COLLISION AVOIDANCE, BIRD HEARING, BIRD CONTROL, ULTRASONIC EFFECTS, ULTRASONIC RESEARCH)

## 1. INTRODUCTION

This report was prepared by the Aircrew Protection Branch, Vehicle Subsystems Division, Flight Dynamics Directorate, Wright Laboratory, Wright-Patterson Air Force Base, Ohio. The effort was performed in-house in support of the USAF Windshield Systems Program Office, USAF Bird/Aircraft Strike Hazard (BASH) Team, and other potential users of an effective device for bird control. The report was written from September to December 1991, by David M. Hamershock, Aircraft Flight Hazard Analyst, Windshield Systems Program Office.

The objective of this report is to assist potential users of UBRDs by providing a principal source of information addressing their efficacy. Potential users of an effective UBRD are many and include: All branches of the military, airfield managers, biologists, pest control/maintenance employees, government agencies (the Federal Aviation Administration, the US Department of Agriculture), agri-/aquaculturalists, aircraft manufacturers, and homeowners.

The USAF, one potential user of an effective UBRD, could repel birds from the airfield environment, preventing hazards to aircraft saving millions of dollars per year. Inhibiting birds from nesting and roosting around static aircraft, aircraft hangars and facilities where they cause disturbing noise, maintenance, corrosion and health problems also can result in saving the USAF money. Since 1987, the USAF has lost six lives, and averaged a loss of \$65 million for 3500 aircraft bird strikes each year (Ron Merritt, USAF BASH Team). 60.3% of reported USAF aircraft bird strikes occur in the airfield environment (Fred Samec, USAF BASH Team [Figure 1]), therefore, finding a method that will lower or evacuate bird populations from the airfield environment is desirable to the USAF.

USAF safety, pest control, base operations, and airfield maintenance personnel often seek methods of repulsing birds from presenting problems to aircraft, airfields, and base facilities. The use of ultrasonics was identified as a possible means of keeping birds away from base facilities or warning them of the approach of an aircraft. If UBRDs can control birds, then US Air Force base bird control and aircraft bird strike problems could be reduced through their applications.

UBRD manufacturers characterize their products as "scientifically sound, humane, inexpensive, and easy to operate" (Bomford and O'Brien 1990) means to deterring birds from inhabiting areas desirable to them. Some UBRD manufacturers also maintain that their mechanisms create unbearable physical stress to a birds' entire body, forcing the bird to flee from the treated area. From medical research, some is known about the possible damaging effects of ultrasonic sound on living organisms at the cellular and tissue levels (Gordon 1967a), but the actual behavioral effects to birds are unknown except for claims

advertised by U Street, Chicago. UBRDs emit sound can't stand the annoying, [but where they protect birds."

It was the basis for acceptance for background diversity of in time of question

## 2. ULTRASONIC

Any sound are designated 29,000 Hz dependent sensitivity to 1939; Kreithen sounds, travel density of 1.2 the right conditions birds, given the incur.

Ultrasonic radiation pressure tissues. Cellular damages. Heat frequency (approximate intensity to in cell dissolution

Radiation movement) with Cell necrosis mitochondria (converting energy ultrasonic irradiation mitochondria by components of

Chemicals ultrasonic irradiation accelerated to and is damaged resulted from (Gordon 1967b)

The great tissues, since

advertised by UBRD manufacturers. Bird-X Inc. (730 West Lake Street, Chicago, Illinois 60606) advertisements claim that their UBRDs emit sounds that are: "Physically harmless, but birds can't stand them . . ., modulations birds can't get used to, annoying, [but] can't injure birds . . ., [and] pitched exactly where they provide intense discomfort to most types of roosting birds."

It was the intent of this effort to establish a validated basis for accepting the manufacturers' assertions. The search for background material resulted in identifying a substantial diversity of investigations that makes further research at this time of questionable value.

## 2. ULTRASONIC CHARACTERISTICS

Any sounds over 20,000 Hertz (Hz) or cycles per second (cps) are designated ultrasonic. Bird sensitivities range from 0.05-29,000 Hz depending upon the species. Human (*Homo sapien*) sensitivity to sound is normally 16-24000 Hz (Brand and Kellogg 1939; Kreithen and Quine 1979; Schwartzkopff 1955a). Ultrasonic sounds, travel at 340 m/s at mean sea level, 15°C (59°F), and a density of 1.23 kg/m<sup>3</sup> (Kuethe and Chow 1986; Blitz 1967). Under the right conditions there is the potential for UBRDs to repulse birds, given the known damaging effects that ultrasonics can incur.

Ultrasonic sound can create heat, chemical effects, radiation pressure, and nerve disruption within living cells and tissues. Collectively, these effects can cause lethal cell damages. Heat can be produced by ultrasound when it is of high frequency (approaching 1 MHz) and is focused. The heat can reach an intensity that can cause damage to cell components resulting in cell dissolution (Gordon 1967a).

Radiation pressure effects cause "streaming" (rapid fluid movement) within cells that in turn has a part in cell necrosis. Cell necrosis (destruction) can occur because of the rupturing of mitochondria (organelles within the cell responsible for converting energy to a form more usable to the cell) caused by ultrasonic irradiation during electron microscopy. The mitochondria break up, releasing molecules lethal to other components of the cell.

Chemicals effect biological entities when combined with ultrasonic irradiation by chemical reaction rates being accelerated to a point where the cell is chemically suffocated and is damaged (Gordon 1967a). Mutations to bird embryos have resulted from ultrasonic treatment to eggs during incubation (Gordon 1967b).

The greatest effects of ultrasonic sounds are on nerve tissues, since nerve impulses can be blocked along nerve fibers.




Fig. 1. Percentages of all US Air Force aircraft birdstrikes, by phase of flight within the airfield environment and by altitude (0 to 1000 ft AGL), from 1 Jan 85 to 31 Sep 91.

Permanent effects of parts of the effects occur at frequencies extremely

Ultras humans. A pain, and exposure(s) birds also before simi

### 3. BIRD P

Birds evolved with levels of p navigate wh excellent a time percep most bird s 1). Upper some specie significant (Schwartzko

In mos humans. Bi faster than and discern the human e 1968). Doc (*Melopsitta* determine c Starling, H (*Columba li* as they app 1939).

Pigeon perception. Pigeons in Quine and K frequency s produced by auroras, oc use these i perception

Permanent damage can result, causing loss of function of the parts of the organism for which the nerves have control. These effects occur in living tissues when ultrasound is applied at frequencies of 1-3 MHz from highly directional sources at extremely close distances (Gordon 1967a).

Ultrasound at levels above 140 dB has many effects upon humans. A loss of hearing sensitivity (temporary or permanent), pain, and sickness can result from constant or periodic exposure(s) (Beuter and Weiss 1986). It can be inferred that birds also have a threshold of intensity they can withstand before similar physical effects occur.

### 3. BIRD HEARING CHARACTERISTICS

Birds have an extraordinary sensitivity to sound. They have evolved with superior hearing ability to adapt to the higher levels of performance necessary to communicate, hunt, and navigate while in flight. Bird hearing requirements include excellent absolute hearing sensitivity, frequency perception, and time perception (Thorpe 1961). Optimum hearing performance for most bird species is achieved between 1,000 and 4000 Hz (Table 1). Upper limit hearing sensitivity can approach 30,000 Hz in some species (Meyer 1986). Most bird species do not exhibit significant hearing capabilities within the ultrasonic range (Schwartzkopff 1968).

In most cases, birds have greater hearing ability than humans. Birds can discriminate sonic frequency changes 10 times faster than man (Pumphrey 1961) and some (song birds) can produce and discern two modulated sounds or "notes" simultaneously. To the human ear these modulations sound like one note (Greenewalt 1968). Dooling and Searcy (1985) found that Budgerigars (*Melopsittacus undulatus*) have greater ability than humans to determine changes in frequencies. As occurs in humans, European Starling, House Sparrow (*Passer domesticus*), and Rock Dove/Pigeon (*Columba livia*) sound sensitivities have been found to decrease as they approach their upper frequency limit (Brand and Kellogg 1939).

Pigeons have exceptional low-frequency (infrasound) perception. Frequencies as low as 0.05 Hz have been discerned by Pigeons in a sound-isolated chamber. Doppler shift studies by Quine and Kreithen (1981) showed that Pigeons could detect a 1% frequency shift at 20 Hz and a 7% shift at 1 Hz. Infrasounds are produced by natural events such as thunderstorms, earthquakes, auroras, ocean waves, and mountain ranges, therefore, Pigeons may use these infrasound abilities to aide in navigation and weather perception (Kreithen and Quine 1979).

Table 1. Sonic reception range of various birds.

Species	Lower limit (Hz)	Most sensitive (Hz)	Upper limit (Hz)	Reference
Mallard <i>Anas platyrhynchos</i>	300	2000-3000	8000	Trainer (1946)
Canvasback <i>Aythya valisineria</i>	190		5200	Meyer (1986)
Rock Dove/Pigeon <i>Columba livia</i>	50	1800-2400	12000	Wassiljew (1933)
	200		11500	Wever & Bray (1936)
	300		7500	Brand & Kellogg (1939)
	300	1000-2000	5800	Trainer (1946)
	300	1000-4000	5500	Heise (1953)
			5600	Stebbins (1970)
			7300	Harrison & Furumoto (1971)
	0.05		5600	Heinz, et al (1977)
	5			Kreithen & Quine (1979)
			8000	Beuter & Weiss (1986)
Turkey <i>Meleagris gallopavo</i>			6600	Malorana & Schleidt (1972)
Barn Owl <i>Tyto alba</i>			12500	Konishi (1973)
Long-eared Owl <i>Asio otus</i>	100	6000	18000	Schwartzkopff (1955a)
Great Horned Owl <i>Bubo virginianus</i>	60		7000	Meyer (1986)
			7000	Trainer (1946)
Eagle Owl <i>Bubo bubo</i>	60	1000	8000	Trainer (1946)
Greenfinch <i>Chloris chloris</i>			20000	Granit (1941)
European Robin <i>Erithacus rubecula</i>			21000	Granit (1941)

Species
American Crow <i>Corvus brachyrhynchos</i>
American Kestrel <i>Falco sparverius</i>
Chaffinch <i>Fringilla coelestis</i>
Ring-billed Gull <i>Larus delawarensis</i>
Red Crossbill <i>Loxia curvirostris</i>
Budgerigar <i>Melopsittacus undulatus</i>
Horned Lark <i>Eremophila alpestris</i>
House Finch <i>Carpodacus mexicanus</i>
House Sparrow <i>Passer domesticus</i>
Brown-headed Nuthatch <i>Molothrus ater</i>
Red-winged Blackbird <i>Agelaius phoeniceus</i>
Field Sparrow <i>Spizella pusilla</i>
Ring-necked Pheasant <i>Phasianus colchicus</i>
Black-billed Cuckoo <i>Pica pica</i>
Snow Bunting <i>Plectrophenax nivalis</i>

Species	Low. Lim. (Hz)	Most sensitive (Hz)	Upper Limit (Hz)	Reference
American Crow <i>Corvus brachyrhynchos</i>	300	1000-2000	8000	Trainer (1946)
American Kestrel <i>Falco sparverius</i>	300	2000	10000 7400	Trainer (1946) Dooling (1982)
Chaffinch <i>Fringilla coelebs</i>	200	3200	29000	Schwartzkopff (1955a)
Ring-billed Gull <i>Larus delawarensis</i>	100	500-800	3000	Schwartzkopff (1973)
Red Crossbill <i>Loxia curvirostra</i>			20000	Knecht (1940)
Budgerigar <i>Melopsittacus undulatus</i>	40	2000 1800-3800	14000 10000	Knecht (1940) Dooling & Saunders (1975)
Horned Lark <i>Eremophila alpestris</i>	350		7600	Meyer (1986)
House Finch <i>Carpodacus mexicanus</i>			7200	Dooling, et al (1978)
House Sparrow <i>Passer domesticus</i>	675 675		11500 18000 18000	Brand & Kellogg (1939) Granit (1941) Summers-Smith (1963)
Brown-headed Cowbird <i>Molothrus ater</i>			9700	Heinz, et al (1977)
Red-winged Blackbird <i>Agelaius phoeniceus</i>			9600	Heinz, et al (1977)
Field Sparrow <i>Spizella pusilla</i>			11000	Dooling, et al (1977)
Ring-necked Pheasant <i>Phasianus colchicus</i>	250		10500	Meyer (1986)
Black-billed Magpie <i>Pica pica</i>	100	800-1600	21000	Schwartzkopff (1955a)
Snow Bunting <i>Plectrophenax nivalis</i>	400		7200	Meyer (1986)

Phase 2.  
sites and used

Phase 3.  
sites and moved  
control site af

A 10-minut  
randomly accomp  
measured by tim  
time they arriv  
Sunflower seeds  
feeders as bait  
and hung from t  
Seed consumptio  
seeds remaining  
their volume fr

The UBRD u  
Street, Chicago  
and ultrasonic  
box with a puls  
pitch), 1 to 50  
It had an avera  
also had settin  
modulation freq  
(C) for a total  
representations  
pitch-C mode an  
Nicolet analyze  
instructions cl  
m long and 22 m

Phase 1 te  
In mid-November  
pitch-C mode te  
The ultrasonic

At the Pha  
activated in ea  
weeks later Th  
feeder. Phase  
completed in Ja  
treated and con

Phases 1 a  
northeastern Ma  
occurrence of i  
areas during ob

Phase 3 te  
pitches in the  
warehouse site  
were tested tha

Species	Low. lim. (Hz)	Most Sensitive (Hz)	Upper limit (Hz)	Reference
Bullfinch <i>Pyrrhula pyrrhula</i>	100 200	3200 3200	21000 25000	Granit (1941) Schwartzkopff (1949) Schwartzkopff (1952)
Canary <i>Serinus canaria</i>	1100 250	2800	10000 9600	Meyer (1986) Dooling, et al (1971)
Cape Penguin <i>Spheniscus demersus</i>	100	600- 4000	15000	Wever, et al (1969)
Tawny Owl <i>Strix aluco</i>	100	3000- 6000	21000	Schwartzkopff (1955a)
Gull (Species unknown)	50		12000	Beuter & Weiss (1986)
Blue Jay <i>Cyanocitta cristata</i>			7800	Cohen, et al (1978)
European Starling <i>Sturnus vulgaris</i>	700	2000	15000 8700	Brand & Kell-ogg (1939) Trainer (1946) Dooling (1982)

### 3. EXPERIMENTAL SUMMARIES

#### 3.1 Experimental Summary # 1

##### *Efficacy Testing of an Ultrasonic Bird Repeller* Richard E. Griffiths (1987)

#### Materials and Methods

Phase 1. Selected two areas with high levels of bird activity. Baited one area and observed it until bird feeding levels off. Recorded number of birds, species composition, and duration of visits for five days. Actuated the ultrasonic device, and recorded bird data until their behavior stabilized. Repeated for the second area, except without the ultrasonic device, to provide a control. A decrease in recorded activities suggested repellency. No change suggested ineffectiveness. A change in, followed by a return to, normal behavior signified habituation.



Phase 2. Repeated Phase 1, except used two other study sites and used the ultrasonic device before baiting.

Phase 3. Repeated Phase 1, except used two other study sites and moved the ultrasonic device from the treatment to the control site after a sufficient amount of time.

A 10-minute sampling interval was chosen. Observations were randomly accomplished during daylight hours. Feeding time was measured by timing randomly selected individual birds from the time they arrived to the test site to the time they departed. Sunflower seeds were inserted into cylindrical plastic bird feeders as bait. The feeders were 6 cm in diameter, 40 cm long, and hung from tree limbs approximately 2 m above the ground. Seed consumption was determined by measuring the height of the seeds remaining in the feeders at dusk, each day and subtracting their volume from the total capacity of the feeder.

The UBRD used, manufactured by Bird-X, Inc. (730 West Lake Street, Chicago, IL), could produce a complex mixture of sonic and ultrasonic sounds. It was a small (8 x 8 x 12 cm) aluminum box with a pulsed output in three ranges: 5 to 50 kHz (low pitch), 1 to 50 kHz (loud pitch), and 20 to 50 kHz (high pitch). It had an average peak output of 112 dB measured at 0.3 m. It also had settings for what the manufacturer called a "high rate modulation frequency" (mode) at 0 Hz (A), 1 kHz (B), and 4 kHz (C) for a total of nine possible sound outputs. Graphic representations of the principal sound outputs tested (high pitch-C mode and loud pitch-C mode) as measured by a model 660B Nicolet analyzer are shown (Figs. 2 and 3). The manufacturer's instructions claimed effective outdoor coverage within an area 30 m long and 22 m wide.

Phase 1 test sites were baited in mid-October 1985. In mid-November the ultrasonic device was activated, the high pitch-C mode tested first and the loud pitch-C mode second. The ultrasonic device was placed 9 m from the feeders.

At the Phase 2 test sites, the ultrasonic device was activated in early October 1985. The feeders were baited two weeks later. The ultrasonic device was placed 3 m from the feeder. Phase 1 type tests (bait before ultrasonics added) were completed in January and February 1986 at this site, except the treated and control site observations were made alternately.

Phases 1 and 2 were both conducted in forest-edge habitat in northeastern Maryland. Both phases did not consider the occurrence of individual birds leaving and returning the test areas during observation periods.

Phase 3 testing was completed using high, low, and loud pitches in the A, B, and C modes at a southeastern Virginia warehouse site in June 1985. House sparrows (*Passer domesticus*) were tested that were perching on electrical wires before

FIGURE 2. Ultrasonic device sound output, loud pitch C-mode; an average of 100 pulses were measured at 0.6 m.




FIGURE 3. Ultrasonic device sound output, high pitch C-mode; an average of 100 pulses were measured at 0.6 m.




TABLE 2. Average treatment bas treatment.

Species	
H. Finch	
Junco	
Chickadee	
Nuthatch	
Blue Jay	

TABLE 3. Average treatment.

Location	
Test Site	
Control Site	

entering the

Results

Species included the (Junco hyema Tufted Titmo atricapillus

Phase 1 at the treat operation, f operation, f

TABLE 2. Average feeding time in seconds by species and treatment based on approximately 100 observations per species per treatment.

Species	Treatment				
	Pre-treatment (Nov)	High C (Dec 1-10)	Loud C (Dec 12-25)	Post-treatment (Jan)	Control (Nov-Jan)
H. Finch	50	40	23	12	31
Junco	112	48	111	45	28
Chickadee	4	3	2	3	12
Nuthatch	16	5	10	2	21
Blue Jay	7	3	4	10	8

TABLE 3. Average sunflower seed consumption (in ml) per day by treatment.

Location	Treatment			
	Pretreatment (Nov)	High C (Dec 1-10)	Loud C (Dec 12-25)	Posttreatment (Jan)
Test Site	1872	1954	2098	1230
Control Site	1015	1260	1153	1276

entering the warehouse. No baiting was executed.

### Results

Species recorded feeding at the Phase 1 and 2 test sites included the House Finch (*Carpodacus mexicanus*), Dark-eyed Junco (*Junco hyemalis*), White-breasted Nuthatch (*Sitta carolinensis*), Tufted Titmouse (*Parus bicolor*), Black-capped Chickadee (*Parus atricapillus*) and Blue Jay (*Cyanocitta cristata*).

Phase 1 testing resulted in decreased average feeding time at the treated site for all species during high pitch-C mode operation. When the device was switched to loud pitch-C mode operation, further decrease in House Sparrow and Chickadee

TABLE 4. Average number of birds arriving at the test site per 10-min interval.

Principal Species	Treatment				
	Post-treatment (Nov)	High C (Dec 1-10)	Loud C (Dec 12-25)	Post-treatment (Jan)	Control (Nov-Jan)
H. Finch	61.6	69.9	91.5	54.0	12.8
Junco	5.6	6.4	5.1	10.2	3.8
Chickadee	3.2	3.3	3.6	2.2	7.9
Nuthatch	0.1	0.8	2.3	2.3	1.9
Blue Jay	0.3	1.4	2.6	6.3	17.6
All * Species	70	82	105	79	48

\* Principal and occasional species.

feeding time was recorded (Table 2). Feeding time for all species except Blue Jays remained below pretreatment levels for the month following the tests. Feeding times were highly variable and appeared to be influenced more by inter- and intraspecies conflicts than by the ultrasonic device. Food consumption was not affected by either treatment ( $P = 0.356$  [Table 3]), and the number of birds visiting the site increased ( $P = 0.042$ ). Control site measurements remained constant. Effects of weather changes were constant at both treatment and control sites.

Phase 2 activity and seed consumption levels were initially lowered after high pitch-C mode treatment commenced, however, the discrepancies disappeared over time. The mixed sonic-ultrasonic mode ( $P = 0.014$ ) resulted in less bird visitation than the all ultrasonic mode ( $P = 0.037$ ). The ultrasonic device was not moved during testing. The same birds had access to both the treated and control sites. Phase 3 testing resulted in no differences in house sparrow activity. Observed head movements indicated that they could perceive the low and loud pitches. Some sparrows even approached the device (from the side, not in front of the output speaker) to investigate it.

#### Discussion and Conclusions

Of all the sites and sonic combinations tested, the bird visitation rate was markedly affected only during the sonic-ultrasonic paired treatment. Neither the ultrasonic mode (above

20,000 Hz) or the ultrasonic mode alone were significantly different from the control. These results indicate that the ultrasonic mode alone does not affect the studied birds.

Activation of the feeder by the ultrasonic mode was available to all birds. Birds were interchanged between the constant and the ultrasonic mode by the occurrence of Jays frightened by the presence of finches or by the presence of finches in January.

The use of the ultrasonic mode in experiments with birds and fewer birds.

It is suggested that a sound like sound of birds inhabiting a site is a favorable condition for not recommending the use of ultrasonic devices.

#### 3.2 Experiment 2

##### Ineffectiveness of Ultrasonic Devices

#### Materials and Methods

A small area with an area with a grassy field and a blind was a ribbon on the divisions at midpoint) was either flat or blind. The blind (10 Apr 87).

Treatment alternated between the ultrasonic mode and the control mode. Each division was placed to 150 m (from the blind) of 2630 and 2630.

The (M)

20,000 Hz) or the ultrasonic/audible mode (1 to 50,000 Hz) significantly affected any of the species studied. The results indicate that the ultrasonic device would not work to keep the studied bird species away from an area attractive to them.

Activation of the ultrasonic device prior to the baiting of the feeder resulted in initial deterrence, however, once bait was available bird activity escalated. When control and test sites were interchanged the activity/seed consumption level remained constant. Recording the duration of feeding efforts was obscured by the occurrence of inter- and intraspecies interaction. Blue Jays frightened away all other birds, and sizable concentrations of finches deterred chickadees. House Finch feeding times inversely affected visitation rates. The decline of feeding time in January could have been caused, in part, by increased Blue Jay presence.

The use of time lapse photography would be useful for future experiments of this type. Greater accuracy, less required labor and fewer necessary funds would result.

It is doubtful that the tested device or other devices with like sound output can deter the studied bird species from inhabiting attractive areas. Unless further tests provide more favorable bird repelling results, the tested ultrasonic device is not recommendable (Griffiths 1987).

### 3.2 Experimental Summary # 2

#### *Ineffectiveness of a Sonic Device for Deterring Starlings* MARY BOMFORD (1990)


##### Materials and Methods

A small test area without obstacles was selected, to provide an area without sound shadows. A 150 m circular area within a grassy field in Canberra, Australia was utilized. A 7 m high blind was at the midpoint (Fig. 4). The circle was divided by ribbons on pegs into 12 (30 degree) segments. Alternate divisions and a concentric inner circle (50 m radius from the midpoint) were selected as buffer zones. All the test area was either flat or gently sloping, therefore, easily visible from the blind. The grass was mowed upon commencement of the experiment (10 Apr 87).

Treated, buffer, and untreated (control) divisions were alternated around the circle. The ultrasonic device speakers were placed at the inner margins of the 3 treated divisions. Each division was divided into 2 parts: 50 m to 112 m and 112 m to 150 m (from the midpoint). These two subdivisions had areas of 2630 and 2607 (square meters) respectively.

The (Model 825) Hi-tec Electronic Scarecrow (Hi-tec Control

Fig. 4. Study plot for starling experiment with a sonic scarecrow, Canberra, Australia, 1987.



Syst. Prop  
 representa  
 control un  
 remote spe  
 units had  
 ultrasonic  
 battery re  
 held 1 m a  
 perimeter,  
 Barriers 2  
 bales were  
 the ultras  
 According  
 hectares  
 automatic  
 1800 each  
 using a so  
 Jersey).

Feedi  
 stale brea  
 margin of  
 served to  
 practice o  
 fresh bait  
 apples (ha  
 day, bait  
 quantified

Indiv  
 x 40 binoc  
 50." Star  
 1600. Eac  
 therefore,  
 hour. On  
 continued

Three  
 remaining  
 a three fa  
 without di  
 (pretreatm  
 data was a  
 Plots of n  
 an ordered  
 [Payne 198

Results

The u  
 directiona  
 range of t  
 the usual

Syst. Propriety Ltd., Australia) was erected by a company representative on 30 Apr 87. The scarecrow consisted of a control unit with a programmable timer to which a number of remote speaker units were connected. The individual speaker units had 5 vertically mounted transducer heads producing the ultrasonic sound. Power was provided by a 12-volt long storage battery recharged by 2 (42 W) solar panels. Each speaker unit, held 1 m above the ground by a steel post, was focused toward the perimeter, along the central axes of each treated division. Barriers 2 m high, 0.4 m thick, and 5 m long made out of hay-bales were constructed behind and beside each speaker to restrict the ultrasonic sound dispersal to only the desired divisions. According to the manufacturer, each speaker will protect 4 hectares (nearly 8 times the area of one division). The automatic timer was set to operate the control unit from 0600 to 1800 each day. The sonic output of each speaker was measured using a sonograph (Kay digital sonograph 7800, Pine Brook, New Jersey).

Feeding quadrats (4 square meters each), with fruit and stale bread (bait) dispersed within, were 30 m from the inner margin of each subdivision. Bait placement from 13-23 Apr 87 served to interest European Starlings into the study area and to practice counting them. From 24 Apr-17 May 87, at 0900 each day, fresh bait consisting of 10 slices of white bread and 10 red apples (halved) were placed within each quadrat. At 1600 each day, bait remaining within each quadrat was collected and quantified to the nearest half (slice of bread or apple).


Individual starlings were counted, from the blind, using 10 x 40 binoculars. Large groups were approximated by "10, 20, or 50." Starting 24 Sep 87, counts were taken each day from 1500-1600. Each division was enumerated at 1 minute intervals, therefore, the 12 divisions were counted 60 times within the hour. On 6 May 87 the scarecrow was turned on and the counting continued through 17 May 87.

Three response variables were measured: Starling numbers, remaining apples, and remaining bread. The data was analyzed by a three factor analysis of variance including scarecrow (with and without divisions), distance (near and far divisions), and period (pretreatment and treatment) as factors. Before analysis, the data was averaged for the pretreatment and treatment periods. Plots of residuals for the three response variables (compared to an ordered distribution generated by the GLIM statistical package [Payne 1986]) were found to be normally distributed.

## Results

The ultrasonic signal emitted from each speaker was highly directional in the vertical plane, encompass the entire 32 kHz range of the sonograph (a substantial amount of it above 16 kHz, the usual upper auditory limit for starlings [Schwartzkopff 1955,

FIGURE 5. Sound spectrogram of the glide-tone section (A) and pulsed section (B) of the signal emitted by a Hi-tec Electronic Scarecrow in the lower frequency ranges. Note that the time scale differs for the two records.



Frings and Cook 1964, Spear 1966]), and consist of a complex 6 second glide tone followed by 10 seconds of pulsed bands at several frequencies (Fig. 5). The glide/pulse sequence repeated continuously with frequency and pattern varying slightly each time.

Microphone readings taken in front of a speaker found the discharged sound to average 91 dB at 10 m, 76 dB at 30 m, and <71 dB at 50 m (by the 50 m point ambient sounds coming from a road and a research station 600 m away proved more intense).

Starlings feeding when the scarecrow was first operated did not appear startled, alarmed, or more alert. None of the birds evacuated immediately from the treated divisions. Within 5 minutes a flock of >500 starlings alighted and began feeding in

TABLE 5. M bread, aver effectiveness 1987.

Treatment	
Treated se	Pretrea
	period
	Near
	Far
Treatme	period
	Near
	Far
Untreated	Pretrea
	period
	Near
	Far
Treatme	period
	Near
	Far

front of a s alighted wi when a heli approached, alarm calls

Starlin (Table 5) an conducted ( period, no s far division untreated d

Other M took bread: Ravens (*Corv melanorhampl boundaries n compared to*



TABLE 5. Numbers of starlings and remaining apples and slices of bread, averaged for days and fields, in an experiment to test the effectiveness of a sonic deterrent device in Canberra, Australia, 1987.

Treatment (n = 3)	Number of starlings		Number of apples		Number of bread slices	
	x	SE	x	SE	x	SE
<u>Treated segments</u>						
Pretreatment period						
Near fields	793	195.5	7.5	0.23	3.3	0.40
Far fields	1307	368.9	6.2	0.93	2.8	0.93
Treatment period						
Near fields	1705	147.8	2.9	0.74	1.7	0.47
Far fields	1586	218.2	2.7	0.54	1.3	0.64
<u>Untreated segments</u>						
Pretreatment period						
Near fields	997	119.0	6.2	0.66	3.0	0.39
Far fields	1001	292.9	6.4	0.87	2.8	0.35
Treatment period						
Near fields	1638	321.5	2.6	0.54	1.2	0.42
Far fields	1197	360.6	3.0	0.86	1.6	0.72

front of a speaker. During the treatment period, starlings often alighted within 1 or 2 m of the speakers to feed. In comparison, when a helicopter, or bird of prey flew over, or a person approached, the birds would take off delivering audible alarm calls.

Starling numbers increased over the course of the experiment (Table 5) and were highest while the treatment period was being conducted ( $F = 6.40$ ; 1,16 df;  $P = 0.022$ ). During the treatment period, no significant differences in numbers between near and far divisions ( $F = 0.0005$ ; 1,16 df;  $P = 0.98$ ) or treated and untreated divisions ( $F = 0.63$ ; 1,16 df;  $P = 0.44$ ) occurred.

Other bird species occasioned all divisions and sometimes took bread: Australian Magpies (*Gymnorhina tibicen*), Australian Ravens (*Corvus coronoides*), and White-winged Choughs (*Corocorax melanorhamphus*). The number of non-starlings inside the test boundaries never exceeded 10 individuals, and was usually <5, compared to an average of 256 starlings, therefore, feeding by

other species should not have biased food removal assessments. Fewer bread slices ( $F = 13.72$ ; 1,16 df;  $P = 0.002$ ) and apples ( $F = 55.31$ ; 1,16 df;  $P < 0.001$ ) remained during the treatment period than during the pretreatment period. During the treatment period, no significant differences ( $P > 0.59$ ) in food amounts remaining between near and far divisions or treated and untreated divisions occurred.

### Conclusions

The Hi-tec Electronic Scarecrow had no effect on the number of and the quantity of food eaten by starlings visiting the 3 treated divisions. In the treatment period, starling numbers were 57% higher than the pretreatment period. Flocks of starlings flew through treated divisions to feeding quadrats without apparent hesitation or avoidance behavior (Bomford 1990).

### 3.3 Experimental Summary # 3

#### *Effect of Ultrasonic, Visual, and Sonic Devices on Pigeon Numbers in a Vacant Building* PAUL P. WORONECKI (1988)

#### Materials and Methods

The Bird-X Ultrason UET-360 (Bird-X Inc., Chicago IL) ultrasonic bird repelling device was evaluated. The device was powered by 110-140 V, could be switched to emit either continuous or pulsed sounds, had an electronic oscillator tuned to 18,000 to 23,000 kHz, and was attached to a turntable that rotated twice a minute. The device output was measured by a B&K Precision Sound Level Meter placed directly in front of the device speaker at a vacant parking lot, within an enclosed metal building, and at 22 unobstructed test site positions.

The UET-360 was tested in a vacant power house building (PH-1) occupied by >70 pigeons at NASA, Plum Brook Station, near Sandusky, Ohio. The floor space of PH-1 was 704 m<sup>2</sup> (roughly 22 m x 32 m). The ceiling was 18 m high. The UET-360 advertisement claims that the bird repelling coverage exceeds 8,000 m<sup>2</sup>, not including secondary coverage.

Other PH-1 features included an open network of concrete pillars, catwalks, platforms, stairs, and railings. Pigeon activity was limited to the upper 4.6 m of the building; nesting on the ledge of the interior wall and roosting on ledges, railings, pipes, and light fixtures. Most pigeons utilized a broken window at the southwest corner as an entrance and exit, which provided for a simple and accurate census.

The UET-360 was suspended by chains and cable 4.6 m from the ceiling. The device was 7.3 m from (and at the same elevation

TABLE 6. So  
with a B&K S  
evaluation c  
1986.

#### Location

DWRC  
(parking  
lot)

Sandusky  
(metal  
building)

Sandusky  
(Power  
House-1)

as) the ledge  
from the wal

Testing  
pigeons inha  
building's se  
from and per  
counter app  
was also not  
least 3 time  
other than s  
changes resu

The UET-  
instructions  
and non-flyin  
was operated  
pulsed output  
measured aga  
numbers cont

#### Results

The cont  
modulation a  
during the pu  
level measur  
after the exp

TABLE 6. Sound level responses from an Ultrason UET-360 taken with a B&K Sound Level Meter at 3 m before, during, and after an evaluation conducted at Sandusky, Ohio, in October and November 1986.

Location	Sound level (decibels)			
	Continuous		Pulsed	
	Impulse	Peak	Impulse	Peak
DWRC (parking lot)	95	101	96	101
Sandusky (metal building)		100		101
Sandusky (Power House-1)		96		98

as) the ledge utilized for nesting, and 11.9, 7.3, and 18.6 m from the walls.

Testing was accomplished 8 Oct-26 Nov 86. The number of pigeons inhabiting PH-1 was counted by 1 person approaching the building's southwest corner (starting 46 m away). Birds leaving from and perched/nested inside the building were counted as the counter approached and entered the building. Nesting activity was also noted. These counts were made between 0730 and 1000 at least 3 times a week. Additional inspections were made at times other than scheduled to make note of any behavioral or activity changes resulting from the device.

The UET-360 was installed according to manufacturers instructions, therefore, all nests (including eggs, nestlings, and non-flying young) were removed before testing. The device was operated continuously for 20 days (20 Oct-7 Nov 86); 10 days pulsed output and 10 days continuous output. Sound output was measured again. The device was then switched off and pigeon numbers continued to be recorded for 10 more days.

## Results

The continuous output was 19.2 kHz, with a slight amplitude modulation at 120 Hz. The device emitted 79 pulses per minute during the pulsed output at frequencies of 20-26 kHz. Sound level measurements taken at a distance of 3 m before, during, and after the experiment yielded similar results. The impulse sound

TABLE 7. Mean number of pigeons counted leaving Power House-1 during Ultrason UET-360 evaluation.

Dates	Treatment Period	Number of Pigeons			No. of Observ.
		x	SD	Range	
8-17 Oct	Pretreatment	64	8.2	52-73	5
18-28 Oct (b)	Pretreatment	66	21.0	31-89	7
29 Oct-7 Nov	Ultrasonic-Continuous	75	15.1	48-92	6
8-17 Nov	Ultrasonic-Pulsed	73	15.3	55-93	5
18-26 Nov	Posttreatment	71	16.7	51-93	7

levels were approximately 5 dB lower. The peak sound level measurements, taken at 22 locations inside PH-1 at distances of 3 to 28 m, varied from 73-98 dB. Levels in the area of pigeon roosting and nesting activity ranged from 73-98 dB for the pulsed output and 84-98 dB for the continuous output. In areas of PH-1 where the device was not visible, background levels from 70-73 dB were recorded. Sound pressure wave measurements revealed that the ultrasonic signals were easily shadowed by objects and that there were areas within PH-1 where the pigeons could easily elude the sounds.

A 10-day pretreatment period (8-17 Oct 86) of counts resulted in an average of 64 pigeons per observation (Table 7). A 11-day pretreatment period (18-28 Oct 86) testing the impact of nest removal and UET-360 presence (without being turned on) upon the PH-1 pigeon population, resulting in an average of 66 pigeons per observation.

UET-360 output in the "continuous" mode began on 29 Oct 86 at 0940 and lasted until 7 Nov 86. After the device was turned on (from a switch outside the building) 10 pigeons left the building within the first fifteen minutes. An average of 75 pigeons were present per observation.

The "pulsed" mode, was tested from 8-17 Nov 86. No change in pigeon presence was noticed as there was an average of 73 pigeons per observation. Four nests had been reconstructed during the treatment periods, 7.3-20.4 m from the UET-360. Eggs were found in the 4 nests when checked on 11 Nov 86 and by 17 Nov there was a total of 8 eggs being incubated.

During a 10-day posttreatment period, from 18-26 Nov 86, an average of 71 pigeons were observed. Two eggs had hatched by 26

Nov 86.

Discussion and

The Ultrasonic response, non day treatment incubated eggs

A sonic the Deva-Spin Saltney Engine numbers when numbers for 2 effects for c

The UET-360 behavior, and vacant buildings are ineffect

#### 4. OTHER STUDIES

Meylan in high level mid-September sunflower field than normal domesticus) and completely. singly and on After the device "gregariously" damaged. The second pulses approximately (1987). Meylan methods to g factors such sources were

Fitzwater bird repellent ultrasonic device "sound shadow" that decrease

Martin a ultrasound up birds were us fecal remains dock employee

## Discussion and Conclusions

The Ultrason UET-360 invoked neither an initial fright response, nor any reduction in pigeon numbers during the two 10-day treatment periods. Pigeons fabricated nests, laid eggs and incubated eggs 7.3-20.4 m from the device.

A sonic device, the Deva-Megastress II, and a visual device, the Deva-Spinning Eyes (both manufactured by Brakam Miller, Saltney Engineering Limited) both had some effect on pigeon numbers when tested within PH-1. The sonic device reduced numbers for 2 of 10 days, whereas the spinning eyes had repelling effects for only the first of 10 days.

The UET-360 failed to reduce the population, alter the behavior, and stop the nesting activity of pigeons within a vacant building. This study demonstrates that ultrasonic devices are ineffective in reducing pigeon populations (Woronecki 1988).

## 4. OTHER STUDIES ON ULTRASONICS

Meylan (1978) conducted an "ultrasonic" experiment resulting in high levels of bird repelling success. From mid-August to mid-September 1977, Meylan tested an ultrasonic device in a sunflower field in Switzerland. Damage to the crop was 40% less than normal during device operation. House Sparrows (*Passer domesticus*) and Tree Sparrows (*Passer montanus*) disappeared completely. Greenfinches (*Carduelis carduelis*) visited the crop singly and only for short time intervals during device operation. After the device was turned off the Greenfinches again fed "gregariously," and within a few days the crop was heavily damaged. The sound produced by the device consisted of one second pulses at 16,776 Hz (Table 8). This frequency level is approximately 3300 Hz below the "ultrasonic" range (Griffiths 1987). Meylan includes no description of his materials and methods to give greater credibility to his experiment. Important factors such as weather, migration, and other available food sources were not included.

Fitzwater (1970) described his experiences using ultrasonic bird repelling devices as "discouraging." He found that ultrasonic devices are expensive to purchase and operate, produce "sound shadows" (leaving areas untreated), and produce sounds that decrease rapidly in magnitude once they leave the source.

Martin and Martin (1984) researched the effects of ultrasound upon cormorants, gulls, and Rock Doves. The tested birds were using shipyard pier towers for roosting at night. The fecal remains left by the birds created a slippery hazard for dock employees and cleaning problems because of the sun baking

TABLE 8. Researchers, ultrasonic frequencies, birds, and results of experiments testing the performance of ultrasonic bird repelling devices.

Researcher	Frequency (kHz)	Bird(s) Tested	Results
Beuter & Weiss	20-50	Gull European Starling	No effect.
Bomford	20-32	European Starling	No effect.
Fitzwater			Discouraging expense, range, and performance.
Griffiths	20-50	House Finch Dark-eyed Junco White-breasted Nuthatch Tufted Titmouse Blue Jay	No effect, except for small effect during ultrasonic/sonic test.
Kerns	20-26	Cliff Swallow	No effect.
Martin & Martin		Cormorant Gull Rock Dove (Pigeon)	5% reduction in bird presence.
Meylan	16.8**	House Sparrow Tree Sparrow Greenfinch	House and tree sparrow populations reduced 100%. Greenfinches reduced significantly.
Theissen, et al	20	Peking duck (Mallard)	No effect.
Woronecki	20-26	Rock Dove (Pigeon)	No effect.

\*\* Not considered an ultrasonic frequency.

them upon metal surfaces (of ships . . .). The ultrasonic devices were placed on top of pier towers and operated for 16 days straight. In comparison to a preultrasound measurement of birds present, there was only a 5% drop in birds present.

Beuter and Weiss (1986) tested UBRDs on gulls (Laridae) at a municipal purification plant. The UBRD emitted ultrasonic frequencies of 20-50 kHz at intensities of up to 135 dB. There was no indication that the gulls could either hear or be repelled

by the d  
scare th  
modulati  
of 60 dB  
these si

The  
feeding  
testing t  
conclude  
intensiti

Eval  
Cliff Swa  
(1985).  
Cliff Swa

A pa  
eliminate  
Florida,  
occurred  
apparent

Bird  
completed  
efficacy  
however,  
customer  
Mona Zems  
informati

5. CONCL

No UB  
population  
had signif  
16776 Hz.  
studied, m  
ultrasonic

A bir  
can focus  
deliver a  
birds' ear  
intensity,  
effects.  
of emitted  
intensity.

UBRDS  
effectiven  
presence o  
birds away

by the device. They did find that an efficient sound signal to scare the gulls had a frequency span of 2-7 kHz, frequency modulation of 0.5-20 Hz, duration of 20 s and minimum intensity of 60 dB. European Starlings also could be repelled by utilizing these signals.

Theissen, et al (1957) studied the effects of UBRDs on the feeding of Peking Ducks (selectively bred Mallards). After testing the feeding behaviors of 30 ducks within a pen, it was concluded that the ducks "do not respond to 20000 Hz sounds at intensities up to 130 dB."

Evaluation of the effectiveness of the "Ultrason ET" UBRD on Cliff Swallows (*Hirundo pyrrhonota*) was accomplished by Kerns (1985). The device lacked significant effect to controlling Cliff Swallow population size or behavior.

A pair of rotating 21000 Hz UBRDs were reported to have eliminated Rock Doves from roosting sites at a building in Florida, however, after a period of four months, habituation had occurred and the Rock Doves would perch atop the UBRDs without apparent discomfort (Dubco 1984 and Dugger 1984).

Bird-X, Inc. was invited to submit any research efforts completed by themselves or any other person(s) addressing the efficacy of UBRDs. Bird-X had no research efforts to submit, however, offered information from numerous records of UBRD customer satisfaction and success (telephone conversation with Mona Zemsky, Bird-X, Inc. Marketing Manager, January 1992). No information was available as to duration of time of UBRD success.

## 5. CONCLUSIONS

No UBRD experiments, to present, have resulted in a bird population reduction greater than 5%. The one experiment that had significant effect utilized a sub-ultrasonic frequency of 16776 Hz. Of the bird species that have had their hearing levels studied, most (26 of 33) do not have the capability of hearing ultrasonic sound (Table 1).

A bird cannot be physically stressed by an UBRD unless it can focus a frequency approaching/above 1 MHz to a birds' body or deliver a sound intensity of over 140 dB at the location of the birds' ear. The physical effects of UBRDs are minimized by the intensity, proximity, and focusing required to cause such effects. Of the UBRDs that have been tested, the maximum levels of emitted sounds recorded include a frequency of 50 kHz and an intensity of 135 dB.

UBRDs (as with most bird control devices) lose their effectiveness over time because birds habituate (get used) to the presence of their repelling qualities. Any sound which scares birds away is often effective only for a limited time, depending

upon the resolve of the bird species being treated. Birds will continue to inhabit busy, noisy, turbulent airfield environments as long as the benefits of available resources outweigh the stress, unpredictability, and threat of physical harm caused by a sonic repelling device.

The results of the research efforts referenced in the report make it difficult to conclude that the claims made by UBRD manufacturers are valid. One possibility for these results is that the tested UBRDs have been designed and advertised by the manufacturers to repel birds that cannot hear ultrasonic sound (Pigeons, European Starlings, Gulls, etc.). Since it is possible for some bird species to hear ultrasonic sound (Chaffinches, Bullfinches, Tawny Owls, etc.), it can be theoretically assumed that these species may be able to be repelled by an UBRD designed specifically for the control of them. Research focusing on bird species with known ultrasonic hearing capabilities may provide data that may improve UBRD performance to the point where an UBRD can selectively repel these species of birds (see Table 1).

This compilation of tests of UBRD performance should enable potential users to make improved decisions on the role of UBRDs in managing their bird control problems. The alternate "active" bird control methods sanctioned by USAF Regulation 127-15 (*The Bird Aircraft Strike Hazard [BASH] Reduction Program*) are: Pyrotechnics, bioacoustics, depredation, propane cannons, scarecrows, bird models, remote-control airplanes, and falconry. While delivering effective performances, these control techniques all have limitations, difficulties, and inefficiencies that result in the continuation of the aircraft birdstrike problem and other bird related problems. Before purchase, potential users of UBRDs should contact existing users of UBRDs to evaluate the duration of their bird control success.

## 6. RECOMMENDATIONS

The information available addressing the frequency perception ability of most bird species is incomplete and often repetitive. As of now only 33 of 9000 (both figures approximate) bird species have been tested to determine their hearing frequency limits, leaving a substantial amount of information yet to be recorded (Welty and Baptista 1986). Research accomplished to record the frequency sensitivities of many untested bird species should be continued. Emphasis should be placed on investigating a broad spectrum of bird classifications. These records would provide UBRD researchers and manufacturers with a more complete basis on which to hypothesize whether an UBRD will render an effective treatment. The compilation of new and existing bird frequency perception information into a single source would be useful for future bird/ultrasonic research efforts.

The need to find an ultimately effective, affordable, easy

to use and e  
research int  
Effective bi  
the needs of  
airfields, f  
any other lo  
problems.

## REFERENCES

- Beuter, K. J.  
systems  
signals
- Blitz, J. 19  
in Brown  
biology  
Springfi
- Bomford, M.  
deterri
- Bomford, M. a  
damage c  
Wildl. S
- Brand, A. R.  
starling  
Bulletin
- Cohen, S. M.,  
threshol
- Dooling, R. J.  
birds. P  
vertebra
- Dooling, R. J.  
130 in K  
communic
- Dooling, R. J.  
parakeet  
critical  
vocalizat
- Dooling, R. J.  
auditory  
undulatus
- Dooling, R. J.  
Auditory  
(*Serinus*
- Dooling, R. J.  
sensitivi  
pusilla).
- Dooling, R. J.  
sensitivi  
vocalizat  
Comp. Phys
- Dubco, T. 198  
The Miami
- Dugger, C. W.



to use and easy to maintain bird repelling method makes future research into possible bird control solutions a necessity. Effective bird control methods need to be capable of fulfilling the needs of the many possible applications: Aircraft, airfields, farmlands, buildings, hangars, docks, ships, signs, or any other locations where roosting or flying birds may cause problems.

#### REFERENCES

- Beuter, K. J. and R. Weiss. 1986. Properties of the auditory systems in birds and the effectiveness of acoustic scaring signals. Meet. Bird Strike Comm. Eur. 8:60-73.
- Blitz, J. 1967. The properties of ultrasound waves. Pages 1-26 in Brown, B. and D. Gordon, eds. Ultrasound techniques in biology and medicine. Charles C. Thomas Publisher, Springfield, Illinois.
- Bomford, M. 1990. Ineffectiveness of a sonic device for deterring starlings. Wildl. Soc. Bull. 18:151-156.
- Bomford, M. and P. H. O'Brien. 1990. Sonic deterrents in animal damage control: a review of device tests and effectiveness. Wildl. Soc. Bull. 18:411-422.
- Brand, A. R. and P. P. Kellogg. 1939. Auditory responses of starlings, english sparrows, and domestic pigeons. Wilson Bulletin 51(1):38-41.
- Cohen, S. M., W. C. Stebbins, and D. B. Moody. 1978. Auditory thresholds of the blue jay. Auk 95:563-568.
- Dooling, R. J. 1980. Behavior and psychophysics of hearing in birds. Pages 261-288 in Comparative studies of hearing in vertebrates. Springer-Verlag, New York.
- Dooling, R. J. 1982. Auditory perception in birds. Pages 95-130 in Kroodsma, D. E. and E. H. Miller, eds. Acoustic communication in birds, Vol. 1. Academic Press, New York.
- Dooling, R. J., and J. C. Saunders. 1975. Hearing in the parakeet (*Melopsittacus undulatus*): absolute thresholds, critical ratios, frequency differentiation limens, and vocalizations. J. Comp. and Physiol. Psych. 88(1):1-20.
- Dooling, R. J., and M. H. Searcy. 1985. Nonsimultaneous auditory masking in the budgerigar (*Melopsittacus undulatus*). J. Comp. Psych. 99(2):226-230.
- Dooling, R. J., R. J. Mulligan, and J. D. Miller. 1971. Auditory sensitivity and song spectrum of the common canary (*Serinus canarius*). J. Acoust. Soc. Am. 50:700-709.
- Dooling, R. J., S. Peters, and M. H. Searcy. 1979. Auditory sensitivity and vocalizations of the field sparrow (*Spizella pusilla*). Bull. Psychonomic Soc. 14:106-108.
- Dooling, R. J., S. R. Zoloth, and J. R. Baylis. 1978. Auditory sensitivity, equal loudness, temporal resolving power and vocalizations in the house finch (*Carpodacus mexicanus*). J. Comp. Physiol. Psych. 92:867-876.
- Dubco, T. 1984. Shriek devices test tough courthouse pigeons. The Miami News (12 Nov.).
- Dugger, C. W. 1984. Noise routs courthouse pigeons. The Miami

- Herald (15 Nov.).
- Fitzwater, W. D. 1970. Sonic systems for controlling bird depredations. Proc. 5th Bird Cont. Sem. 5:110-119.
- Frings, H. and B. Cook. 1964. The upper frequency limits of hearing in the European starling. Condor 66:56-60.
- Gordon, D. 1967a. Biological effects below cavitation level. Pages 154-158 in Brown, B. and D. Gordon, eds. Ultrasound techniques in biology and medicine. Charles C. Thomas Publisher, Springfield, Illinois.
- Gordon, D. 1967b. Mutations and ultrasound. Pages 220-246 in Brown, B. and D. Gordon, eds. Ultrasound techniques in biology and medicine. Charles C. Thomas Publisher, Springfield, Illinois.
- Granit, O. 1941. Beitrage zur Kenntnis des Gehörsinnes der Vogel. Ornis Fennica 18:49-71.
- Greenewalt, C. H. 1968. Bird song: acoustics and physiology. Smithsonian Institution Press, Washington, D. C.
- Griffiths, R. E. 1987. Efficacy testing of an ultrasonic bird repeller. Pages 53-63 in S. A. Schumake and R. W. Bullard, eds. Vertebrate pest control and management materials: 5th volume. ASTM Spec. Tech. Publ. 974, Philadelphia, Pa.
- Harrison, J. B. and L. Furumoto. 1971. Pigeon audiograms: comparison of evoked potentials and behavioral thresholds in individual birds. J. Aud. Res. 11:33-42.
- Heinz, R. D., J. M. Sinnott, and M. B. Sachs. 1977. Auditory sensitivity of the red-winged blackbird (*Agelaius phoeniceus*) and brown-headed cowbird (*Molothrus ater*). J. Comp. Physiol. Psych. 91:1365-1376.
- Heise, G. A. 1953. Auditory thresholds in the pigeon. Am. J. Psychol. 66:1-19.
- Kerns, J. D. 1985. Evaluation of the effectiveness of the "Ultrason ET" ultrasonic device as a means of cliff swallow control. Natural Resources Report No. 85-2. Fort Wainwright, Alaska.
- Knecht, S. 1940. Über den Gehörsinn und die Musikalität der Vogel. Zeitschr. vergl. Physiol. 27:169-232.
- Konishi, M. 1973. How the barn owl tracks its prey. Am. Sci. 61:414-424.
- Kreithen, M. L. and D. B. Quine. 1979. Infrasound detection by the homing pigeon: a behavioral audiogram. J. Comp. Physiol. 129:1-4.
- Kuethel, A. M. and C. Y. Chow. 1986. Foundations of aerodynamics/bases of aerodynamic design, 4th edition. John Wiley & Sons, New York. 555 pp.
- Maiorana, V. A. and W. M. Schleidt. 1972. The auditory sensitivity of the turkey. J. Aud. Res. 12:203-207.
- Martin, L. R. and P. C. Martin. 1984. Research indicates propane cannons can move birds. Pest Control 52(4):52.
- Meyer, D. B. 1986. The avian ear and hearing. Pages 48-59 in P. D. Sturkie, ed. Avian physiology: 4th edition. Springer-Verlag, New York.
- Meylan, A. 1978. Granivorous birds in sunflower crops. Proc. Vertbr. Pest Conf. 8:73-77.
- Pumphrey, R. J. 1961. Sensory organs: hearing. Pages 69-86 in

Marsha  
birds.  
Quine, D. B.  
discr  
Dopple  
Schwartzkop  
Vibrat  
31:527  
Schwartzkop  
347.  
Schwartzkop  
XI con  
Verlag  
Schwartzkop  
the au  
A. V.  
verteb  
Schwartzkop  
R. Kir  
Academ  
Spears, P. J.  
of the  
Contro  
Stebbins, W.  
the mo  
psych  
experi  
Summers-Smi  
251 pp  
Thiessen, C  
H. R.  
peking  
Soc. A  
Theissen, C  
thresh  
Thorpe, W.  
commun  
in exp  
Press,  
Trainer, J.  
D. The  
Wassiljew,  
für di  
Welty, C. W.  
Saunde  
Wever, E. G.  
studie  
Comp.  
Woronecki,  
device  
vacant  
ACKNOWLEDGE  
Russ Urzi,  
Short, Tom

- Marshall, A. J. ed. *Biology and comparative anatomy of birds*. Academic Press, New York.
- Quine, D. B. and M. L. Kreithen. 1981. Frequency shift discrimination: can homing pigeons locate infrasounds by Doppler shifts? *J. Comp. Physiol.* 141:153-155.
- Schwartzkopff, J. 1949. Über Sitz und Leistung von Gehör und Vibrationssinn bei Vögeln. *Zeitschr. vergl. Physiol.* 31:527-608.
- Schwartzkopff, J. 1955a. On the hearing of birds. *Auk* 72:340-347.
- Schwartzkopff, J. 1955b. Schallsinnesorgan bei Vögeln. In *Acta XI congressus internationalis ornithologici*. Berhauser Verlag, Basel and Stuttgart.
- Schwartzkopff, J. 1968. Structure and function of the ear and the auditory brain areas in birds. Pages 41-59 in DeReuck, A. V. S. and J. Knight, eds. *Hearing mechanisms in vertebrates*. Little, Brown, Boston, Massachusetts.
- Schwartzkopff, J. 1973. Mechanoreception. In Farner, D. S., J. R. King, and K. C. Parkes, eds. *Avian biology*, Vol. 3. Academic Press, New York.
- Spear, P. J. 1966. Bird control methods and devices; comments of the National Pest Control Association. *Proc. Bird Control Semin.* 3:134-146.
- Stebbins, W. C. 1970. Studies of hearing and hearing loss in the monkey. Pages 41-66 in Stebbins, W. C., ed. *Animal psychophysics: the design and conduct of sensory experiments*. Appleton, Century, Crofts, New York.
- Summers-Smith, D. 1963. *The house sparrow*. Collins, London. 251 pp.
- Thiessen, G. J., E. A. G. Shaw, R. D. Harris, J. B. Gollop, and H. R. Webster. 1957. Acoustic irritation threshold of peking ducks and other domestic and wild fowls. *J. Acoust. Soc. Am.* 29:1301.
- Theissen, G. J. and E. A. G. Shaw. 1957. Acoustic irritation threshold of ringbilled gulls. *J. Acoust. Soc. Am.* 29:1307.
- Thorpe, W. H. 1961. *Bird song: the biology of vocal communication and expression in birds*. Cambridge monographs in experimental biology, No. 12. Cambridge University Press, London and New York.
- Trainer, J. E. 1946. *The auditory acuity of certain birds*. Ph. D. Thesis, Cornell Univ., Ithaca, NY.
- Wassiljew, P. 1933. Über das Unterscheidungsvermögen der Vogel für die höhen Tone. *Zeitschr. vergl. Physiol.* 19:424-438.
- Welty, C. W. and L. Baptista. 1988. *The life of birds*, 4th ed. Saunders College Publishing, New York. 581 pp.
- Wever, E. G. and C. W. Bray. 1936. Hearing in the pigeon as studied by the electrical responses of the middle ear. *J. Comp. Psych.* 22:353-363.
- Woronecki, P. P. 1988. Effect of ultrasonic, visual, and sonic devices on pigeon numbers devices on pigeon numbers in a vacant building. *Proc. Vertebr. Pest Conf.* 13:266-272.
- ACKNOWLEDGEMENTS** Thank you: Ralph Speelman, Duncan Dversdall, Russ Urzi, Ron Merritt, Bob Dogan, David Rubin, Fred Samec, Jeff Short, Tom Seamans, Paul Woronecki and Jeannie Stewart.

ABSTRACT:

Twenty-eight percent of all USAF bird strikes occurred during low-level flight operations between 1987 and 1991. These strikes resulted in more than \$250 million in damage, the destruction of four aircraft, and five aircrew fatalities. Low-level airspace evaluation once focused only on the Bird Avoidance Model (BAM), which is a useful tool for estimating waterfowl hazards. However, additional bird species not modelled by the BAM, such as raptors, gulls, cranes, and pelicans also pose significant hazards to aircraft operations. Hazards associated with these species are being examined separately using known bird population and migration dynamics. To reduce hazardous and costly bird strikes to aircraft, the USAF BASH Team is updating the BAM. The new BAM will calculate the relative risk of a bird strike by integrating biological and geographical data into a Geographic Information System (GIS). The GIS is allowing detailed analyses of robust databases, including the North American Breeding Bird Survey (BBS), Bird Banding Recovery, Christmas Bird Count (CBC), Hawk Migration Association of North America (HMANA), and Refuge databases which have helped verify bird distribution and abundance in the BAM. The USAF BASH Team will continue to enhance the BAM through the future addition of weather components and the integration of bird recognition data provided by the Next Generation Weather Radar (NEXRAD). NEXRAD will provide a near real-time bird avoidance capability for low-level aircraft operations.

Banding Rec  
BAM. The e

**Low-Level Airspace Bird Strike Hazard Evaluation and Using of  
GIS to Integrate Bird Population Dynamics Into an Aircraft Bird  
Avoidance Model**

**BACKGROUND:** The United States Air Force (USAF) reports more than 3,000 bird aircraft collisions each year. Approximately 28% of USAF bird strikes from 1987 to 1991 occurred during the low-level and range phases of flight. These strikes caused a disproportionate amount of damage, due to higher aircraft operating speeds, and resulted in the destruction of four aircraft, five aircrew fatalities, and greater than \$250 million in damage. In the early 1980's, the Bird Aircraft Strike Hazard (BASH) Team developed a predictive risk model to identify areas and times associated with high bird strike risk. The Bird Avoidance Model (BAM) estimates the probability of a bird strike along a low-level training route by distributing a density of birds into a volume of space and sweeping the frontal surface area of an aircraft through that space. The BAM has been a useful tool for estimating waterfowl (ducks, geese, and swans) hazards, but other birds considered hazardous to military aircraft operations were not incorporated into the model. Birds such as raptors (birds of prey), gulls, cranes, and pelicans are evaluated separately using known population and migration dynamics, however these data for many species remain incomplete.

**CURRENT RESEARCH:** The BASH Team has recognized the necessity of incorporating these potentially hazardous bird species as well as terrain features associated with increased bird activity into a new Bird Avoidance Model. The current BAM program lacks the flexibility to add species, update databases of dynamic biological systems, and incorporate geophysical data. The use of Geographic Information System (GIS) technology offers the ideal solution for integrating these spatial data. Data to be incorporated into the model will include bird species' weights, flock densities, a relative aircraft damage factor, and species' behavioral differences. The temporal aspects of the hazards, including time of year (seasonal variation) and time of day (diurnal variation) and associated altitude components will be included in the risk assessment. The BAM output, provided to military flight and mission planners, will include a graphical depiction of bird hazards and a text file with recommendations for aircraft operations in the vicinity of the hazard. Modelling efforts for the continental United States are currently underway using Geographic Resource Analysis Support System (GRASS). GRASS is a public domain GIS developed by the U.S. Army Corps of Engineers Construction Engineering Research Lab (USACERL). This raster-based GIS, run on a UNIX-based operating system, is ideally suited to analyze biological distribution data and provides the flexibility to add species and calculate risk based on selected criteria.

Geographically referenced population and migration dynamics for waterbirds, raptors, cranes, pelicans, gulls, and blackbirds are being collected from state and federal agencies and are entered into a Dbase III+ file. The GRASS GIS has allowed easy analysis of robust databases such as The Hawk Migration Association of North America (HMANA), North American Breeding Bird Survey (BBS), Christmas Bird Count (CBC) and Bird

**FUTURE RE**  
data and ultin  
Radar (NEXI  
waterfowl, gu  
system will pr  
Europe, and v  
aircraft operat

The US Air F  
operations out  
a result of per  
Belgium, The  
geophysical an  
significantly in  
this effort in F  
extremely haza  
effort. The BA  
establishing co

Banding Recovery to aid in the verification of bird distributions and abundance in the BAM. The expanded BAM is scheduled for completion in September 1993.

FUTURE RESEARCH: The BAM can be supported by bird movement and altitudinal data and ultimately weather components supplied by the Next Generation Weather Radar (NEXRAD) system, once it becomes operational. Recognition algorithms for waterfowl, gull, and blackbirds for NEXRAD have been developed. The NEXRAD system will provide coverage for most of the United States and a large section of Europe, and will furnish a near real-time bird avoidance capability for low-level military aircraft operations.

The US Air Force experiences a significantly higher bird strike rate during low-level operations outside the United States. In Europe, low-level bird advisories are issued as a result of personal observations and observations of air defense radars located in Belgium, The Netherlands, and Germany. The integration of these advisories along with geophysical and biological databases, with a predictive model based on GRASS will significantly improve flight safety. The BASH Team hopes to begin collecting data for this effort in Fall of 1992. Deployments into regions such as the middle east, with extremely hazardous bird migrations, emphasized the need for a global-scale modelling effort. The BASH Team is searching for global migration path information and establishing contacts with European and global GRASS users.